

PRO-MAX SERIES



POLYCHAIN BELT MODELS

Standard Features:

Revolutionary aircraft grade aluminum frame, life-time warranty, easy access tip holder/ gun holder/hose hanger on handle, epoxy powder coated finish (lifetime warranty), 10,000 hour rated Gates poly - chain cogged belt (2 year warranty), 50 mesh inlet water filter, EZ - Start unloader valve, low oil shut-down, engine oil drain, oversize pneumatic tires, dual spring cushioned shock absorbing feet, 3 / 4" cold rolled steel axle, H D low speed pump and thermo - sensor (prevents overheating in bypass mode). Note: 8 and 10 g.p.m. units set up for tank feed. All units are completely factory assembled and tested in the USA.

Standard Accessories:

All units include: gun/ wand assembly w/quick connects, 50' Gates hose w / quick connect, Maxi-Flo 20% chemical injector assembly w/ quick connect, 4 color - coded quick connect hp spray nozzles, and 1 color-coded chemical nozzle. Note: Chemical injector is optional on 5000, 6000 & 7000 psi units (See Available Options).

Available Options:

1. Skid Mount (No wheels) Call for pricing
2. Non Marking Hose
3. Block Mounted K7 Unloader.
4. ACI5000 5000 PSI Chem Injector Assembly.
5. ACI6000 6000 PSI Chem Injector Assembly.
6. *Electric Start Option. Note: All electric start units include " battery ". 18, 20 & 24 h.p. Honda, 25 hp. & 27 hp. Kohler engines are electric start only and include auxiliary fuel tank.
7. 13 hp. Honda
8. 16 hp. Vanguard

Don't See It? Gasoline, Electric or Diesel Powered.
Call - We Specialize in Custom Units

POLYCHAIN BELT DRIVE	
MODEL	DESCRIPTION
2000 (MAX.) PSI	
B1520KCEA125	15.0 GPM @ 2000 psi - 27 hp. Kohler* w/ CAT pump
2800 (MAX) PSI	
B1228KGEAI05	12.0 GPM @ 2800 psi - 30 hp. Kohler w/ GP pump
3000 (MAX) PSI	
B8030HAEA306	8.0 GPM @ 3000 psi - 20 hp. Honda* w/ AR pump
B8030HGEA306	8.0 GPM @ 3000 psi - 20 hp. Honda* w/ GP pump
B1030KCEAI05	10.0 GPM @ 3000 psi - 27 hp. Kohler* w/ CAT pump
B1030KGEA390	10.8 GPM @ 3000 psi - 27 hp. Kohler* w/ GP pump
3500 (MAX) PSI	
B4035HCP307	4.0 GPM @ 3500 psi - 13 hp. Honda w/ CAT pump
B4035HG303	4.0 GPM @ 3500 psi - 13 hp. Honda* w/ GP pump
B5535HAEA309	5.5 GPM @ 3500 psi - 18 hp. Honda* w/ AR pump
B5535HGEA303	5.5 GPM @ 3500 psi - 18 hp. Honda* w/ GP pump
B8035HAEA306	8.0 GPM @ 3500 psi - 24 hp. Honda* w/ AR pump
B8035HGEA306	8.0 GPM @ 3500 psi - 24 hp. Honda* w/ GP pump
4000 (MAX.) PSI	
B4040HG303	4.0 GPM @ 4000 psi - 13 hp. Honda w/ GP pump
B4540HCEA307	4.5 GPM @ 4000 psi - 18 hp. Honda* w/ CAT pump
B5540HAEA309	5.5 GPM @ 4000 psi - 20 hp. Honda* w/ AR pump
B5540HGEA303	5.5 GPM @ 4000 psi - 20 hp. Honda w/ GP pump
5000 (MAX) PSI	
B4550HAEA511	4.5 GPM @ 5000 psi - 20 hp. Honda* w/ AR pump
B4550HCEA511	4.5 GPM @ 5000 psi - 20 hp. Honda* w/ CAT pump
B4550HGEA511	4.5 GPM @ 5000 psi - 20 hp. Honda* w/ GP pump
B5550HAEA515	5.5 GPM @ 5000 psi - 24 hp. Honda* w/ AR pump
B5550HGEA511	5.5 GPM @ 5000 psi - 24 hp. Honda* w/ GP pump
6000 (MAX) PSI	
B4560HGEA600	4.5 GPM @ 6000 psi - 24 hp. Honda* w/ GP pump
B5060KGEA600	5.0 GPM @ 6000 psi - 27 hp. Kohler* w/ GP pump
7000 (MAX) PSI	
B4070HAEA700	4.0 GPM @ 7000 psi - 24 hp. Honda* w/ AR pump
B4550HCEA511	4.0 GPM @ 7000 psi - 24 hp. Honda* w/ GP pump



High speed surface cleaners can increase efficiency and get the job done 50% faster than with gun alone. Easy to operate and ideal for most flat surfaces. Long wands can eliminate use of ladders for safety.