

PRO-MAX SERIES



ELECTRIC BELT DRIVE MODELS

Standard Features:

Revolutionary aircraft grade aluminum frame, life-time warranty, easy access tip holder/ gun holder/hose hanger on handle, epoxy powder coated finish (lifetime warranty), 10,000 hour rated Gates poly - chain cogged belt (2 year warranty), 50 mesh inlet water filter, EZ - Start, adjustable pressure unloader, pneumatic tires, dual spring cushioned shock absorbing feet, 3 / 4" cold rolled steel axle, H D low speed pump and thermo - sensor (prevents over-heating in bypass mode), TEFC motors w/ overload protection, complete control assembly w/Mag starter, thermal overload, and start-stop buttons in NEMA 12 enclosure w/12' wire (no plug). All units are completely factory assembled and tested in the USA.

Standard Accessories:

All units include: gun/ wand assembly w/quick connects, 50' Gates hose w / quick connect, Maxi-Flo 20% chemical injector assembly w/ quick connect, 4 color - coded quick connect hp spray nozzles, and 1 color-coded chemical nozzle.

Note: Chemical injector is optional on 5000, 6000 & 7000 psi units (See Available Options).

ELECTRIC BELT DRIVE	
MODEL	DESCRIPTION
2000 PSI	
B4020EIA303	4 GPM @ 2000 psi - 5 hp./230V/1PH/25A w/ AR pump
B4020EICP307	4 GPM @ 2000 psi -5 hp./230V/1PH/25A w/ CAT pump
B4020EIG303	4 GPM @ 2000 psi - 5 hp./230V/1PH/25A w/ GP pump
B4020EA303	4 GPM @ 2000 psi - 5 hp./230V/3PH/12A w/ AR pump
B4020E3CP307	4 GPM @ 2000 psi -5 hp./230V/3PH/12A w/ CAT pump
B4020E3G303	4 GPM @ 2000 psi - 5 hp./230V/3PH/12A w/ GP pump
3000 PSI	
B4030EIA303	4 GPM @ 3000 psi -7.5 hp./230V/1PH/33A w/ AR pump
B4030EICP307	4 GPM @ 3000 psi -7.5 hp./230V/1PH/33A w/ CAT pump
B4030EIG303	4 GPM @ 3000 psi -7.5 hp./230V/1PH/33A w/ GP pump
B4030EA303	4 GPM @ 3000 psi -7.5 hp./230V/3PH/17A w/ AR pump
B4030E3CP307	4 GPM @ 3000 psi -7.5 hp./230V/3PH/17A w/ CAT pump
B4030E3G303	4 GPM @ 3000 psi -7.5 hp./230V/3PH/17A w/ GP pump
3500 PSI	
B4035EIG303	4 GPM @ 3500 psi -10 hp./230V/1PH/40A w/ GP pump
B4035E3A303	4 GPM @ 3500 psi -10 hp./230V/3PH/23A w/ AR pump
B4035E3CP307	4 GPM @ 3500 psi -10 hp./230V/3PH/23A w/ CAT pump
B4035E3G303	4 GPM @ 3500 psi -10 hp./230V/3PH/23A w/ GP pump
B5535E3A309	5.5 GPM @ 3500 psi -15 hp./230V/3PH/34A w/ AR pump
B5535E3C307	5.5 GPM @ 3500 psi -15 hp./230V/3PH/34A w/ CAT pump
B5535E3G303	5.5 GPM @ 3500 psi -15 hp./230V/3PH/34A w/ GP pump
B8035E3G100	8 GPM @ 3500 psi -20 hp./230V/3PH/40A w/ GP pump
4000 PSI	
B3540E1A303	3.5 GPM @ 4000 psi -10 hp./230V/1PH/40A w/AR pump
B4040E3A303	4 GPM @ 4000 psi - 15 hp./230V/3PH/34A w/AR pump
B4040E3G303	4 GPM @ 4000 psi - 15 hp./230V/3PH/34A w/GP pump
B4540E3C307	4.5 GPM @ 4000 psi -15 hp./230V/3PH/34A w/CAT pump
5000 PSI	
B4550E3G511	4.5 GPM @ 5000 psi -20 hp./230V/3PH/46A w/GP pump
B5550E3G511	5.5 GPM @ 5000 psi -20 hp./230V/3PH/46A w/GP pump
6000 PSI	
B4560E3G600	4.5 GPM @ 6000 psi - 20 hp./230V/3PH/46A w/GP pump
7000 PSI	
B4070E3A615	4.0 GPM @ 7000 psi - 20 hp./230V/3PH/46A w/AR pump

Available Options:

1. Skid Mount (No wheels) Call for pricing
2. Non Marking Hose
3. Block Mounted K7 Unloader.
4. ACI5000 5000 PSI Chem Injector Assembly.
5. ACI6000 6000 PSI Chem Injector Assembly.
6. *Auto Start/Stop (230V).