



STANDARD FEATURES

- **BELT DRIVE TRIPLEX PLUNGER PUMP—GENERAL®**
- **OIL FIRED BURNER - WAYNE®**
OIL FIRED (NO. 1 & NO. 2 DIESEL, KEROSENE, NO. 1 HOME HEATING OIL)
- **WHEEL CONFIGURATIONS FOR BV OIL FIRED UNITS**
PNEUMATIC-TUBE AXLE WHEELS FRONT AND REAR
- **UPSTREAM CHEMICAL INJECTION**
- **SPLIT STAINLESS-STEEL OUTER COIL WRAP**
- **STEEL CHASSIS**
WITH TEXTURED POLYESTER POWDER COAT
- **FUEL TANK, 9 GALLON CAPACITY**
WITH INTEGRATED CAP GAUGE AND
STAINLESS-STEEL DIAL INDICATOR
- **OIL FIRED UNITS - 36' GFCI POWER CORD**
- **TRIGGER GUN CONTROL**
WAND ASSEMBLY WITH COOL GRIPS
- **NOZZLE (0°, 15°, 25°, 40°)**
- **50' HOSE — 3/8" ID**
INSULATED WIRE BRAID HOSE
WITH SWIVEL CONNECTOR
- **COIL: SCHEDULE 80**
- **ADJUSTABLE THERMOSTAT**
- **MAGNETIC STARTER**
- **POLYETHYLENE FLOAT TANK**
- **36' GFCI POWER CORD ON SINGLE PHASE**